

**PERMANENT WAY
NOTES**

CHAIRS (8) MISC.

THESE NOTES ARE INTENDED FOR THE GUIDANCE AND ASSISTANCE OF STAFF ENGAGED UPON PERMANENT WAY WORK. THEY DO NOT IN ANY WAY MODIFY, SUPPLEMENT OR AMEND THE INSTRUCTIONS LAID DOWN IN E.O.I, STANDARD DRAWINGS CIRCULARS ETC., WHICH SHOULD BE REFERRED TO IN ALL CASES.

BS 95R ORDY. (S) WT. 46 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SERRATED BASE

SEATING DEPTH $1\frac{1}{4}$ "

R. 1396

OO ORDY. WT. 52 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SERRATED BASE

SEATING DEPTH $1\frac{3}{16}$ "

R. 673

BS 95R S.T. WT. 52 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SERRATED BASE

SEATING DEPTH $1\frac{1}{4}$ "

R. 1512

OO S.T. WT. 58 1/2 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SERRATED BASE

SEATING DEPTH $2\frac{1}{16}$ "

R. 1699

BS 95R J WT. 53 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SERRATED BASE

SEATING DEPTH $1\frac{3}{4}$ "

R. 975

OO S.T. 3-H WT. 57 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{2}$ "

SERRATED BASE

SEATING DEPTH $2\frac{1}{16}$ "

1/4" DIA. HOLES FOR B.S. 6 3/8 x 8" CHAIR-SCREWS & FERRULES

R. 3560

BS 95R LI (S) WT. 47 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SERRATED BASE

SEATING DEPTH $1\frac{3}{4}$ "

ALSO USED FOR OO SEC.

R. 1532

OO PIT WT. 54 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{4}$ "

ALSO USED FOR B.S. 95 RAILS

SEATING DEPTH $1\frac{3}{4}$ "

SN. 31188
R. 1306

BS 95R MI. (S) WT. 44 LB.

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{3}{8}$ "

SERRATED BASE

SEATING DEPTH $1\frac{3}{4}$ "

ALSO USED FOR OO SECTION.

R. 2092 * ONLY AVAILABLE WITH 1/4" & 1/8" (S2) SEATING DEPTH.

OO Z WT. 46 LB

HEIGHT OF BOSS ABOVE CHAIR-BASE $1\frac{1}{8}$ "

SEATING DEPTH $1\frac{3}{16}$ "

ALSO USED FOR BS 5 SECTION

SN 18405

N.B. CHAIRS MARKED (S) AVAILABLE WITH SEATING DEPTH INCREASED BY 1/16" INCREMENTS TO MAXIMUM OF 3/8".
E.G. BS 95 ORDY (S12) WHERE INCREASED SEATING IS 3/4" & TO SEATING IS 2 1/2".